



## SPECIAL FEATURES

- AC input range selected by switch
- High efficiency
- DC adjust range
- LED Power indicated
- Output reverses protection
- Free air cooling convection
- 230\* 115\* 50 mm
- Weight 0.9 kgs/pcs
- 1 year warranty

## SPECIFICATION

### Output

- Maximum power.....200 Watts
- DC adjust range.....  $\pm 5\%$  of rating output voltage
- Hold-up time.....> 20 ms at 230Vac/ 50Hz
- Over Voltage Protection...115% ~ 150% of rated output
- Over Power Protection.....110% ~ 200%, auto-recovery
- Short Circuit Protection.....shut off, AC recycle to restart
- Connector.....9P / 9.5mm pitch terminal block

### Input

- Input range.....90~132Vac/180~264Vac selected by switch
- Frequency.....47-63Hz
- AC inrush current...Cold start, 30A @ 115Vac; 60A @ 230Vac
- EMI/RFI.....FCC Part 15J, Class A & CISPR 22 Class A

### Operating temperature

- 0 °C to +30 °C @100%; 40 °C @ 90%; 50 °C @ 80% load
- Storage temperature: -20 °C to +80 °C
- Free air cooling convection

Model	IM201C12-1M	IM201C24-1M
Output	V1	V1
Voltage	+12V	+24V
Max. Load	16.5A	8.3A
Efficiency	>80% @115Vac/60 Hz	>80% @ 115 Vac/60 Hz